

		CTS Cement Manufacturing Corporation 11065 Knott Avenue, Suite A Cypress, CA 90630 Phone: (800) 929-3030 • Fax: (714) 379-8270 info@ctscement.com www.ctscement.com
---	---	---



Concrete Pharmacy® FIBER — MSDS
March 2010

 [Concrete Pharmacy® FIBER - MSDS \[Printable PDF\]](#)

SECTION I — GENERAL INFORMATION

1. CTS Cement Manufacturing Corporation | Rapid Set® Products
11065 Knott Avenue, Suite A
Cypress, CA 90630
2. Emergency Phone Number: (800) 929-3030
3. Website: www.ctscement.com
4. Chemical Name and Synonyms: N/A
5. Trade Name and Synonyms: Fiber
6. Class: Additive

SECTION II — PHYSICAL DATA

7. Boiling Range: N/A
8. Melting Point: 300°F, 149°C
9. Vapor Pressure: N/A
10. Vapor Density: N/A
11. Specific Gravity: 0.90 (water = 1)
12. H₂O Soluble: Insoluble
13. Evaporation Rate: N/A
14. Appearance and Odor: Short clear fibers with no apparent odor

SECTION III — FIRE AND EXPLOSION HAZARD DATA

15. Flash Point: (Method Used) N/A
16. Explosive Limits: N/A
17. Extinguishing Media: Water spray, dry chemical foam CO₂, or Halon
18. Special Fire-Fighting Procedures: Wear NIOSH/MSHA-approved for class A fires.
19. Unusual Fire and Explosion Hazards: Hazardous products of combustion: resulting combustion products will vary from fire to fire, depending on factors such as temperature, air supply and other materials present.

SECTION IV — HEALTH HAZARD DATA

20. Effects of Overexposure:

Eyes — No
Skin — No
Inhalation — No
Ingestion — No

21. Chronic Overexposure Information: Extreme overexposure by inhalation of the ignited material is the only condition which might necessitate emergency or first-aid procedures.

SECTION V — EMERGENCY AND FIRST-AID PROCEDURES

22. Eyes: Immediately flush with potable water for a minimum of 15 minutes. Seek medical attention.
23. Skin: Flush with copious amounts of water.
24. Inhalation: Remove to fresh air. Seek medical attention.